

Specifications:

Model	Power	Air Tank Capacity Litre / Gal	Maximum Pressure	Voltage/Frequency	Air Displacement		speed (R. P. M)	N. W. /G. W. KGS	Packing mm
					Litre / Min	CFM			
HRS-G350-5L	350W/0.45HP	5L/1.3Gal	8Bar / 125PSI	220V/50Hz	88	3.11	1400/1700	16/17.5	490*410*320
HRS-G280-4L	280W/0.37HP	4L/1.05Gal	8Bar / 125PSI	220V/50Hz	58	2.05	1400/1700	11.5/13	380*370*350
HRS-G1500-18L	1500W/2.0HP	18L/4.8Gal	10Bar / 145PSI	220V/50Hz	250	8.83	1400/1700	43.5/46	600*580*580
HRS-G200-5L	200W/¼HP	5L/1.3Gal	7Bar / 115PSI	220V/50Hz	32	1.13	2800/3360	12.5/14	415*340*340
HRS-G750-6L	750W/1.0HP	6L/1.6Gal	8Bar / 125PSI	220V/50Hz	135	4.77	1400/1700	19.5/21	460*420*390
HRS-G550-6L	550W/0.75HP	6L/1.6Gal	8Bar / 125PSI	220V/50Hz	135	4.77	1400/1700	19.5/21	440*410*410
HRS-M150-3L	200W/0.2HP	3L/0.8/Gal	1.28Bar / 57PSI	220V/50Hz	23	0.81	1400/1700	5/6	310*135*310

Customization is available for various voltage and frequency

Note: We reserve the right to make design improvements without prior notice. Product specifications are subject to change, and the final specifications may vary depending on the actual machine.